

POSTMIX



Lafarge Postmix is a quality-assured premixed ready to use formulation for fixing all types of fence posts.

GENERAL INFORMATION

Lafarge Postmix is a premixed ready to use product composed of a selected blend of cements and aggregates intended for domestic use.

FEATURES


- Plastic packaging enables it to be stored outside without risk of deterioration
- Simple to use. No mixing required, just add to water
- Sets in 5-10 minutes and then hardens rapidly
- Allows quick fence panel hanging in around 30 minutes

APPLICATIONS

Postmix fixes all types of wood, metal and concrete posts in all types of soil.


Postmix should only be used for fixing posts and should not be used for any other purpose.

IDEAL FOR:



POST FIXING

WEATHER RESISTANT PACKAGING



AVAILABILITY

Available in 20kg plastic bags.

STORAGE

This product must be stored in unopened bags clear of the ground. All bags must be sheltered from the weather and stored in a frost-free, cool and dry location, avoiding direct contact with the ground. If stored correctly and used within 155 days of the packing date shown on this bag, the activity of the reducing agent* will be maintained and this product will contain, when mixed with water, no more than 0.0002% (2 ppm) soluble chromium (VI) of the total dry weight of cement. Use of this product after the end of the declared storage period (see above) may increase the risk of an allergic reaction.

USAGE GUIDE

1. Dig a hole to the required size for your post.
2. Half fill the hole with water and place the post in the hole.
3. Add Postmix uniformly around the post until it is above the water level.
4. Add additional water if the dry powder is showing.
5. Adjust the post into position and support for approximately 10 minutes until secure.

POST SHAPE & SIZE	HOLE SIZE (WIDTH x DEPTH)	BAGS REQUIRED (APPROX)
Round 2 (50 mm)	6" (150 mm) x 12" (300 mm)	Bag
	6" (150 mm) x 18" (450 mm)	½ Bag
	6" (150 mm) x 24" (600 mm)	¾ Bag
	8" (200 mm) x 12" (300 mm)	Bag
	8" (200 mm) x 18" (450 mm)	1 Bag
Square 3" (75 mm)	8" (200 mm) x 24" (600 mm)	1½ Bags
	8" (200 mm) x 18" (450 mm)	¾ Bag
	8" (200 mm) x 24" (600 mm)	1 Bag
	8" (200 mm) x 30" (750 mm)	1½ Bags
	12" (300 mm) x 18" (450 mm)	2½ Bags
	12" (300 mm) x 24" (600 mm)	3 Bags
Square 4" (100 mm)	12" (300 mm) x 30" (750 mm)	3¾ Bags
	8" (200 mm) x 18" (450 mm)	Bag
	8" (200 mm) x 24" (600 mm)	¾ Bag
	8" (200 mm) x 30" (750 mm)	1 Bag
	12" (300 mm) x 18" (450 mm)	2 Bags
	12" (300 mm) x 24" (600 mm)	2¾ Bags
	12" (300 mm) x 30" (750 mm)	3½ Bags

ADDITIONAL INFORMATION

Technical data and guidelines based on ambient conditions of +20°C and 50% relative humidity. Lower temperatures may prolong and higher temperatures may shorten indicated values.

TECHNICAL SUPPORT

Should you require information for this or any other product within the Lafarge range, please contact our Customer Support team on 01285 646900 or visit our website at:

www.lafargecement.co.uk

HEALTH AND SAFETY

Contact between cement powder and body fluids (e.g. eye fluids) may cause irritation, dermatitis or burns. Cement is classified as an irritant under the Chemicals (Hazard information and Packaging) Regulations. Please refer to the product safety data sheet for full information.

*Added to control the level of soluble chromium (VI)

